

# AIRPORT MASTER RECORD

Data Source: [https://www.faa.gov/air\\_traffic/flight\\_info/aeronav/aero\\_data/](https://www.faa.gov/air_traffic/flight_info/aeronav/aero_data/)

PRINT DATE: 5/22/2026  
AFD EFF 05/14/2026

> 1 ASSOC CITY: ELKO 4 STATE: NV LOC ID: EKO FAA SITE NR: 13048.\*A  
 > 2 AIRPORT NAME: ELKO RGNL 5 COUNTY: ELKO NV  
 3 CBD TO AIRPORT (NM): 01 W 6 REGION/ADO: AWP/PHX 7 SECT AERO CHT: SALT LAKE CITY

### GENERAL

10 OWNERSHIP: PUBLIC  
 > 11 OWNER: CITY OF ELKO  
 > 12 ADDRESS: 975 TERMINAL WAY  
 ELKO, NV 89801  
 > 13 PHONE NR: 775-777-7190  
 > 14 MANAGER: JAMES FOSTER  
 > 15 ADDRESS: 975 TERMINAL WAY  
 ELKO, NV 89801  
 > 16 PHONE NR: 775-777-7194  
 > 17 ATTENDANCE SCHEDULE:

ALL ALL 0500-2100

### SERVICES

70 FUEL: 100LL A  
 71 AIRFRAME RPRS: MAJOR  
 72 PWR PLANT RPRS: MAJOR  
 73 BOTTLE OXYGEN: NONE  
 74 BULK OXYGEN: HIGH/LOW  
 75 TSNT STORAGE: HGR, TIE  
 76 OTHER SERVICES: AMB, CARGO, CHTR, INSTR, RNTL

### OPERATIONS

Information on aircraft operations is available from FAA's Aviation System Performance Metrics <https://aspm.faa.gov>

### FACILITIES

18 AIRPORT USE: PUBLIC  
 19 ARPT LAT: 40-49-29.9950N ESTIMATED  
 20 ARPT LONG: 115-47-28.8150W  
 21 ARPT ELEV: 5139.8 SURVEYED  
 22 ACREAGE: 700  
 > 23 RIGHT TRAFFIC: 06, 12  
 > 24 NON-COMM LANDING: NO  
 25 NPIAS/FED AGREEMENTS: NGY  
 > 26 FAR 139 INDEX: I A S 05/1973

80 ARPT BCN: WG  
 81 ARPT LGT SKED : SEE RMK  
 BCN LGT SKED: SS-SR  
 82 UNICOM: 123.000  
 83 WIND INDICATOR: YES-L  
 84 SEGMENTED CIRCLE: YES  
 85 CONTROL TWR: NO  
 86 FSS: RENO  
 87 FSS ON ARPT: NO  
 88 FSS PHONE NR:  
 89 TOLL FREE NR: 1-800-WX-BRIEF

### RUNWAY DATA

> 30 RUNWAY INDENT:  
 > 31 LENGTH:  
 > 32 WIDTH:  
 > 33 SURF TYPE-COND:  
 > 34 SURF TREATMENT:  
 35 GROSS WT: S  
 36 (IN THSDS) D  
 37 2D  
 38 2D/2D2  
 > 39 PCN:

	06/24	12/30
> 30 RUNWAY INDENT:	7,454	3,015
> 31 LENGTH:	150	60
> 32 WIDTH:	ASPH-G	ASPH-G
> 33 SURF TYPE-COND:	GRVD	NONE
> 34 SURF TREATMENT:	78.0	12.0
35 GROSS WT: S	105.0	
36 (IN THSDS) D	170.0	
37 2D		
38 2D/2D2		

### LIGHTING/APCH AIDS

> 40 EDGE INTENSITY:  
 > 42 RWY MARK TYPE-COND:  
 > 43 VGS: 44 THR COSSING HGT.:  
 45 VISUAL GLIDE ANGLE:  
 > 46 CNTRLN-TDZ:  
 > 47 RVR-RVV:  
 > 48 REIL:  
 > 49 APCH LIGHTS:

	MED			
> 40 EDGE INTENSITY:	PIR - G / PIR - G	BSC - G / BSC - G	- / -	- / -
> 42 RWY MARK TYPE-COND:	P4L / P4L	/	/	/
> 43 VGS:	44 / 51	/	/	/
44 THR COSSING HGT.:	3.00 / 3.25	/	/	/
45 VISUAL GLIDE ANGLE:	N - N / N - N	N - N / N - N	- / -	- / -
> 46 CNTRLN-TDZ:	- N / - N	- N / - N	- / -	- / -
> 47 RVR-RVV:	N / N	N / N	/	/
> 48 REIL:	/ MALSR	/	/	/

### OBSTRUCTION DATA

50 FAR 77 CATEGORY  
 > 51 DISPLACED THR:  
 > 52 CTLG OBSTN:  
 > 53 OBSTN MARKED/LGTD:  
 > 54 HGT ABOVE RWY END:  
 > 55 DIST FROM RWY END:  
 > 56 CNTRLN OFFSET:  
 57 OBSTN CLNC SLOPE:  
 58 CLOSE-IN OBSTN:

	C / D	A(V) / A(V)	/	/
50 FAR 77 CATEGORY	/ 1,036	906 / 143	/	/
> 51 DISPLACED THR:	ROAD / POLE	POLE / POLE	/	/
> 52 CTLG OBSTN:	/	M /	/	/
> 53 OBSTN MARKED/LGTD:	24 / 99	26 / 30	/	/
> 54 HGT ABOVE RWY END:	700 / 2,300	650 / 900	/	/
> 55 DIST FROM RWY END:	325R / 450R	75L / 100L	/	/
> 56 CNTRLN OFFSET:	20:1 / 21:1	17:1 / 23:1	/	/
57 OBSTN CLNC SLOPE:	N / N	N / N	/	/
58 CLOSE-IN OBSTN:				

### DECLARED DISTANCES

> 60 TAKE OFF RUN AVBL (TORA):  
 > 61 TAKE OFF DIST AVBL (TODA):  
 > 62 ACLT STOP DIST AVBL (ASDA):  
 > 63 LNDG DIST AVBL (LDA):

	7,217 / 7,454	3,015 / 3,015	/	/
> 60 TAKE OFF RUN AVBL (TORA):	7,217 / 7,454	3,015 / 3,015	/	/
> 61 TAKE OFF DIST AVBL (TODA):	7,217 / 7,454	3,015 / 3,015	/	/
> 62 ACLT STOP DIST AVBL (ASDA):	7,217 / 7,454	3,015 / 3,015	/	/
> 63 LNDG DIST AVBL (LDA):	7,217 / 6,418	2,109 / 2,872	/	/

### > 110 REMARKS

A 030 RWY 12/30 NOT AVBL FOR PART 121/PART 380 OPS WITH SKED PAX CARRYING OPS MORE THAN 9 PAX SEATS AND NON-SKED PAX CARRYING OPS MORE THAN 30 PAX SEATS.  
 A 039 RWY 06/24 PCR VALUE: 340/F/B/X/T  
 A 039 RWY 12/30 PCR VALUE: 50/F/C/X/T  
 A 043 PAPI RWY 24 DOES NOT PRVD OBSTN CLNC BYD 6.5 NM FM THR.  
 A 070 100LL, A AVAILABLE 24/7.  
 A 081 ACTVT MALSR RWY 24; MRL RWY 06/24 - CTAF. PAPI RWY 06 & 24 ON CONSLY.  
 A 110-001 RWY 24 DESIGNATED CALM WIND RWY.  
 A 110-004 PPR FOR ALL ACFT OPNS OVER 100000 LBS CALL 775-777-7190.  
 A 110-005 TKOF ONLY ON RWY 12. LAND ONLY ON RWY 30.  
 A 110-006 NO TGL RWY 12/30.  
 A 110-007 STEEP SLOPE/GRADIENT RWY 30 UPWARD.  
 A 110-010 SFC CONDS NOT MNT DLY 0500-1400Z.  
 A 110-011 FOR CD IF UNA TO CTC ON FSS FREQ, CTC SALT LAKE ARTCC AT 801-320-2568.  
 A 110-013 COLD TEMPERATURE AIRPORT. ALTITUDE CORRECTION REQUIRED AT OR BELOW -25C.

111 INSPECTOR: ( F ) 112 LAST INSP: 05/09/2025 113 LAST INFO REQ:

# AIRPORT MASTER RECORD

Data Source: [https://www.faa.gov/air\\_traffic/flight\\_info/aeronav/aero\\_data/](https://www.faa.gov/air_traffic/flight_info/aeronav/aero_data/)

PRINT DATE: 5/22/2026  
AFD EFF 05/14/2026



# AIRPORT MASTER RECORD

Data Source: [https://www.faa.gov/air\\_traffic/flight\\_info/aeronav/aero\\_data/](https://www.faa.gov/air_traffic/flight_info/aeronav/aero_data/)

PRINT DATE: 5/22/2026  
AFD EFF 05/14/2026